

The award-winning Audioengine 2 speakers just got better. With a built-in digital-to-analog converter (DAC), the Audioengine 2+ allows you to send high-quality digital audio direct from your computer's USB port.



Features

- Built-in power amplifiers
- Dual analog audio inputs
- USB audio input
- Variable audio output
- High-quality connectors
- Hand-built cabinets
- Power-saving idle mode
- Cables included

Finish options

-  Satin Black
-  Hi-Gloss White

Technical specifications

- Power output** 60W peak power total
(15W RMS / 30W peak per channel), AES
- Amplifier type** Dual class AB monolithic
- Drivers** 2.75" Kevlar woofers, 3/4" silk dome tweeters
- Inputs** 3.5mm stereo mini-jack, RCA, USB
- Outputs** RCA variable line-out
- Main voltages** 110-240V 50/60Hz auto-switching
- SNR** >95dB (typical A-weighted)
- THD+N** <0.05% at all power settings
- Crosstalk** -50dB
- Freq. response** 65Hz-22kHz ± 2.0 dB
- Input impedance** 10K ohms unbalanced
- DAC** TI/Burr Brown PCM2704C
- Input bit depth** up to 16 bits native
- Input sample rate** up to 48KHz native
- USB device class** type 1.1 or above



Back Left (Powered)